

Display Cooler






RF101-100



RF101-101



RF101-102

Model	RF101-100	RF101-101	RF101-102
Description	Display Cooler	Display Cooler (with fan inside and back)	Display Cooler
Capacity (L)	21	21	15
Volts	220~240V/110V 50/60Hz	220~240V/110V 50/60Hz	220~240V/110V 50/60Hz
Power (W)	76	76	76
Refrigerant	R134a/36g	R134a/36g	R134a/35g
Temperature Range	0~10°C	0~10°C	0~10°C
Dimensions (mm)	330x410x472	330x410x472	350x420x360
Certificate			

Absorption Refrigerator



RF180-103



RF180-104

Model	RF180-103	RF180-104
Desciption	Absorption Refrigerator	Absorption Refrigerator
Volts	65	65
Power(W)	110V/60Hz 230V/50Hz	110V/60Hz 230V/50Hz
Door Type	Solid Door	Glass Door
Capacity(L)	30	30
Temperature Range	0~8℃	4~12℃
Color	Matt Black/Dark Gray/ Creamy White (Can Be Customized)	Matt Black/Dark Gray/ Creamy White (Can Be Customized)
Power Consumption	0.85KW.h/24H	1KW.h/24H
Dimensions(mm)	420x400x480	415x400x480
N.W.(kg)	13.2	15.2
Certificate	CE	CE

Absorption Refrigerator



RF180-101



RF180-102



RF180-100



Model	RF180-101	RF180-102	RF180-100
Description	Absorption Refrigerator	Absorption Refrigerator	Absorption Refrigerator
Volts	65	65	80
Power(W)	110V/60Hz 230V/50Hz	110V/60Hz 230V/50Hz	110V/60Hz 230V/50Hz
Door Type	Solid Door	Glass Door	Solid Door
Capacity(L)	40	40	50
Temperature Range	0~8℃	4~12℃	0~8℃
Color	Matt Black/Dark Gray/ Creamy White (Can Be Customized)	Matt Black/Dark Gray/ Creamy White (Can Be Customized)	Matt Black
Power Consumption	0.85KW.h/24H	1KW.h/24H	1KW.h/24H
Dimensions(mm)	440x400x550	435x400x550	510x550x430
N.W.(kg)	14.8	17	18.2
Certificate	CE	CE	CE

Absorption Refrigerator



RF180-105



RF180-106

Model	RF180-105	RF180-106
Description	Absorption Refrigerator	Absorption Refrigerator
Volts	80	80
Power(W)	110V/60Hz 230V/50Hz	110V/60Hz 230V/50Hz
Door Type	Solid Door	Glass Door
Capacity(L)	60	60
Temperature Range	0~8℃	4~12℃
Color	Matt Black/Dark Gray/ Creamy White (Can Be Customized)	Matt Black/Dark Gray/ Creamy White (Can Be Customized)
Power Consumption	1.15KW.h/24H	1.15KW.h/24H
Dimensions(mm)	500x485x560	495x485x560
N.W.(kg)	18.5	20.8
Certificate	CE	CE