

Sous Vide Cooking Baths



CE110-100



CE110-102

Model	CE110-100	CE110-101	CE110-102
Description	Sous Vide Cooking Baths	Sous Vide Cooking Baths	Sous Vide Cooking Baths
Volts	100~240V/50~60Hz	100~240V/50~60Hz	100~240V/50~60Hz
Power (W)	1000	1000	2000
Maximum Temperature	85°C	85°C	85°C
Temperature Constant	+/-0.5°C	+/-0.5°C	+/-0.5°C
Display Resolution	0.1°C	0.1°C	0.1°C
Capacity (L)	8	12	20
Internal Dimensions (mm)	327x265x150	327x265x200	530x327x150
Outer Dimensions (mm)	370x305x310	370x305x310	570x370x310
N.W. (kg)	9.8	10.7	15.5
Certificate	CE	CE	CE

Sous Vide Cooking Baths



CE110-103



CE110-104

Model	CE110-103	CE110-104
Description	Sous Vide Cooking Baths	Sous Vide Cooking Baths
Volts	100~240V/50~60Hz	100~240V/50~60Hz
Power (W)	2000	2400
Maximum Temperature	85°C	85°C
Temperature Constant	+/- 0.5°C	+/- 0.5°C
Display Resolution	0.1°C	0.1°C
Capacity (L)	26	56
Internal Dimensions (mm)	530x327x150	654x530x200
Outer Dimensions (mm)	570x370x310	694x673x310
N.W. (kg)	17	27

Digital Sous Vide



CE160-100



CE160-101

±1°C
· Digital Control

Model	CE160-100	CE160-101
Volts	220~240V/50Hz	220~240V/50Hz
Power (W)	2000	2000
Capacity (L)	16	24
Working Time (H)	0~99	0~99
Working Temperature (°C)	30~90	30~90
Dimensions (mm)	370x340x270	540x340x270
N.W. (kg)	9.2	9.8
Certificate	CE	CE
Remark: 1) 5 preset options,with individual time and temperature setting 2) Drain with hose tube attachment 3)Stainless steel body and stainless steel lid 4)Automatic warm water circulation system 5)Drying and overheating protection 6)Stainless steel wire racks available(to put food in the bowl)		

Sous Vide Immersion Circulator

- *Providing precise and consistent temperature control to cook food evenly
- *Heating up to 30L (8 gallons) water or more
- *Good for usage at home, restaurant, hotel etc for compact kitchen
- *Easy use digital control panel
- *Automatic cooking with setting of desired time and temperature
- *Pump with AD 12V motor
- *Easy to use and apply to all kind of foods
- *Stainless steel construction
- *Quiet operation
- *The easy portable immersion circulator clamps are applicable to any pot or tank with round or flat walls 6" or deeper
- *Low water level alarm
- * NEMA 5-15P plug



CE220-114

Volts	120V/60Hz
Power (W)	1500
Inside Temperature	5~99°C
Control	Manual
Dimensions (mm)	153×64×330
N.W. (kg)	4.1
MOQ (pcs)	200
Certificate	CE In Process